

Typesetting Articles for *Res Philosophica*^{*†}

Boris Veytsman[‡]

2026/08/10, v1.40

Abstract

This package provides a class for typesetting articles for the journal *Res Philosophica*, <http://www.resphilosophica.org>.

Contents

1	Introduction	2
2	User Interface	2
2.1	Commercial Fonts	2
2.2	Invocation and Options	2
2.3	Topmatter	3
2.3.1	Commands for Authors	3
2.3.2	Commands for Editors	4
3	Special Notes	6
3.1	Bibliography	6
4	Implementation	8
4.1	Options	8
4.2	Loading Classes and Packages	9
4.3	Page Dimensions and Paragraphing	11
4.4	Headers	11
4.5	Top Matter Macros	13
4.6	Typesetting Top Matter	16
4.7	Notes	19
4.8	Typesetting End Matter	19
4.9	Sectioning	21
4.10	Additional Commands	22
4.11	The End	23

^{*}©2012–2026, Boris Veytsman

[†]This work was commissioned by the Saint Lois University

[‡]borisv@lk.net, boris@varphi.com

1 Introduction

According to the statement at <http://www.resphilosophica.org/>, *Res Philosophica* is an international, quarterly journal of philosophy that publishes research in all areas of philosophy, historical and topical. Founded as *The Modern Schoolman* by Jesuit Scholastics in 1925, the journal is edited by members of the Philosophy Department at Saint Louis University and supported generously by the College of Arts and Sciences.

This package is intended for the authors and editors of the journal to typeset the articles in L^AT_EX. Note that the journal is typeset in *Linotype Sabon*. The users may buy the fonts and install their free L^AT_EX support [1], or use the options `bodyfont=cm` and `rpfont=cm` to typeset the articles using Computer Modern. Of course, the line and page breaks in the latter case are different from those in the final version typeset with commercial fonts.

2 User Interface

2.1 Commercial Fonts

The package can be used with free Computer Modern fonts or with commercial fonts to mimick the journal typesetting. The installation of additional fonts is therefore fully optional.

Res Philosophica uses Linotype Sabon for the body text and URW Garamond for mathematics. Sabon is a commercial font. URW Garamond is free, but due to license restrictions it is usually not included with T_EXLive, MikT_EX and other major distributives. If you bought Linotype Sabon, you need to install the package `lsabon` [1]. To use URW Garamond, you need to download the `pf` files from a CTAN mirror (<http://mirror.ctan.org/fonts/urw/garamond/>), install them in the directory `fonts/type1/urw/garamond` under `$TEXMFLOCAL` and run `texhash`.

2.2 Invocation and Options

To use the class put in the preamble of your document

```
\documentclass[options]{resphilosophica}
```

The class `resphilosophica` internally loads `amsart`, and therefore all class options for `amsart` are technically valid. However, most of them are not especially meaningful for `resphilosophica`. There are several options specific for this class. They are described below. Note that the class uses key-value interface for some options, for example

```
\documentclass[bodyfont=sabon]{resphilosophica}
```

option The option `bodyfont` can have three values: `sabon` for Sabon/Garamond fonts, **bodyfont** `cm` for Computer Modern and `auto` (default). The later option switches to the use of Sabon if the font metrics are present in your system, and to the use of Computer Modern otherwise.

option The option `manuscript` is intended to facilitate the communications between **manuscript** the editor and the author. It enables two things:

1. The numbering of lines in the manuscript is switched off in the normal mode, but is on in the manuscript mode.
2. The command `\EditorialComment` is no-op in normal mode, but produces mariginal commentaries in the manuscript

option The option `preprint` is for the final version of the manuscript. In this mode `preprint` there are no editorial comments, but the numbering of lines is preserved

option The option `screen` is intended for the screen reading. When this option is `screen` selected, the links become highlighted.

option The option `forthcoming` is like `screen`, but it is used when there is no information about the volume. The macro `\onlinedate{<date>}` can be used to set `forthcoming` `\onlinedate` the date of online publication.

option The preferred solution for bibliography is `natbib` package [2]. The option `natbib` `natbib=true` (default) sets the package and the proper options, including bibliography style. The option `natbib=false` switches this behavior off, and the formatting of the bibliography becomes the full responsibility of the author. The package includes the Bib_{TeX} bibliography style `resphilosophica.bst`.

2.3 Topmatter

Topmatter is the part of the article with the informations about the authors, their affiliations, the publication data, etc.

There are two kinds of top matter commands: the ones used primarily for authors and the ones used primarily for editors. We describe them separately.

2.3.1 Commands for Authors

`\title` The command `\title`, as in `amsart` class, has two arguments: one optional, and one mandatory:

`\title[<ShortTitle>]{<FullTitle>}`

The mandatory argument is the full title of the article. The optional argument, if present, defines the shorter version of the title for running heads. If the optional argument is absent, the full title is used instead.

The title is typeset in small caps. The result of the command `\emph` in title depends on whether commercial fonts and the package `lsabon` package is used: with a relatively recent version of the package `lsabon` the emphasized text is typeset in Small Caps Italics.

`\author` The interface for specifying the authors and their affiliations is close the the `\email` one of `amsart` [3] (and different from the standard L^AT_EX). For each author a `\address` separate command `\author` should be used, followed by `\address` and (optionally) `\curraddr` `\curraddr`, `\email` and `\urladdr`.

`\urladdr` In some cases the authors list may be too long for the running head, even `\shortauthors` if the abbreviated forms are used for each author. In this case it is possible to change the running head by a *redefinition* of the command `\shortauthors`. This redefinition must be done after all `\author` commands, but before `\maketitle`:

`\renewcommand{\shortauthors}{A.~Smith et al}`

`\thanks` Like `amsart` (and unlike standard L^AT_EX), `resphilosophica` allows `\thanks` only *outside* of commands `\title` and `\author`. The text of `\thanks` is typeset at the end of the paper as a footnote marked ‘Acknowledgments’. Note that the right vertical positioning of this footnote might require an additional run of L^AT_EX.

`\titlenote` The `\titlenote{<note>}` command creates a special footnote for the title. This command should be issued *outside* the `\title` command.

`\authornote` The similar `\authornote{<note>}` command creates a special footnote for the author. This command should be issued *outside* the `\author` command.

`\copyrightnote` Normally each paper is copyrighted by the authors and by the journal. This is reflected in the footnote on the first page of the article. However, by arrangement with the editors, certain papers may have different copyright. The command `\copyrightnote{<copyright statement>}`, if issued, changes the footnote to the corresponding text, for example:

```
\copyrightnote{\textcopyright~2012 by the authors. This paper may
be reproduced, in its entirety, for noncommercial purposes.}
```

Note that if you issue this command, you should explicitly include both the copyright sign and the year unless the paper does not have a copyright, for example:

```
\copyrightnote{This paper is in the public domain}
```

`\copyrightyear` Normally the copyright statement includes the year of copyright, which is assumed to be the publication year as specified by the `\publicationyear` command (see below). If this assumption is wrong, you may correct it, for example,

```
\copyrightyear{1998}
```

`abstract (env.)` The abstract of the paper must be put between `\begin{abstract}` and `\end{abstract}`. Unlike the situation in `amsart` class, abstract may be put *after* `\maketitle`.

`\maketitle` The macro `\maketitle` typesets the top matter. All top matter information should be specified before this command.

2.3.2 Commands for Editors

The commands described in this section should be used by the editors to insert the information about the published paper. They must be put before the `\maketitle` command.

`\volumenumber` The macros `\volumenumber`, `\issuenumber`, `\publicationyear`, `\publicationmonth`,
`\issuenumber` `\papernumber`, `\startpage`, `\endpage` set up the corresponding data for the pa-
`\publicationyear` per, for example:
`\publicationmonth`
`\papernumber` `\volumenumber{88}`
`\startpage` `\issuenumber{1--2}`
`\endpage` `\publicationyear{2012}`
`\publicationmonth{January--February}`
`\papernumber{2}`
`\startpage{1}`
`\endpage{39}`

Note that if the argument of `\endpage` is empty, L^AT_EX tries to calculate the last page number as best as it can.

Sometimes publication month for double issues is too long to fit on the back cover. For this case `\publicationmonth` has the optional argument, abbreviated month, for example

```
\publicationmonth[Jan--Feb]{January--February}
```

`\manuscriptid` The command `\manuscriptid[⟨id⟩]` sets the number of the manuscript assigned at submission. If it is set, it is used to calculate the doi number (see below).

`\doinumber` Normally you do not need to set the DOI of the paper: T_EX will construct the number using the paper data. However, you *may* override its decision using the command `\doinumber` which sets the DOI explicitly, for example, `\doinumber{⟨10.5840/resphilosophica.2013.01.01⟩}`. You probably should not use this macro.

`\prevpaper` Instead of setting `\startpage`, one can use the the command `\prevpaper{⟨previous paper⟩}`, with the argument being the location and file name of the previous paper in the journal, for example:

```
\prevpaper{../infinity/concept_of_infinity}
```

Note that the `.tex` suffix should *not* be used. The previous paper must be processed by `latex` prior to the current one. In this case `latex` will read the last page of the previous paper, and start the current one from the proper page number.

`\paperUrl` When a paper is submitted to the Crossref service, which keeps the database of Digital Object Identifiers, its URL is calculated by the script used by editors. The command `\paperURL{⟨url⟩}` overrides this choice.

`\EditorialComment` The macro `\EditorialComment[⟨level⟩]{⟨comments⟩}` typesets the comments on the margins in the `manuscript` mode, for example,

```
Which is a well known fact.\EditorialComment{A citation is
needed}\EditorialComment[1]{Please make the citation more
explicit}.
```

Editorial comments have *levels*. A level can be numeric or symbolic; symbolic levels can contain letters and numbers. The default level is 0, so `\EditorialComment{text}` is equivalent to `\EditorialComment[0]{text}`.

`\ECSelect` The command `\ECSelect{⟨level,level,...⟩}` selects the levels of editorial comments to display in the `manuscript` mode. Note that 0 corresponds to the default level, so the command `\ECSelet{0}` should be used to show these comments.

Sometimes it is useful to tell the author about typesetter's changes in the manuscript. The dialog between the author and typesetter might take several iterations, so the class provides a system for this dialog.

`\TC` The macro `\TC[⟨level⟩]{⟨text⟩}` makes `{⟨text⟩}` highlighted in the `manuscript` mode if the level `[⟨level⟩]` is chosen. For example,

```
This proposition \TC[1]{(first discussed by the author in 2010)} can
be stated as the following.
```

The level can be numerical, or logical, e.g. `\TC[new]{text}`. Actually any combination of letters and numbers that does not contain commas or spaces can be used for level. By default the level is 0, so `\TC{<text>}` is equivalent to `\TC[0]{<text>}`.

`\TCSelect` The decision to highlight certain levels is done by the command `\TCSelect[<color>]{<level,level,level..}`. The first optional argument is the color used for highlighting; by default **magenta**. Actually any color expression understandable by `xcolor` can be used. The second argument is a comma-separated list of levels that will be highlighted by the selected color. The command `\TCSelect` can be repeated, for example,

```
\TCSelect{0,1,new}
\TCSelect[blue]{second-level}
```

If a level does *not* appear in any `\TCSelect` command, it is not highlighted—that is why we do not need a separate `\TCOff` command.

3 Special Notes

notes (*env.*) Some authors include special notes, for example, bibliography description, that precede list of references, but follow the signature block. The environment **notes** is intended for this purpose. It has one mandatory argument, title, for example

```
\begin{notes}{Bibliography notes}
  The best discussion of the problem can be found in...
\end{notes}
```

3.1 Bibliography

As mentioned above, **resphilosophica** by default uses **natbib** [2]. You should use **natbib** commands like `\citet`, `\citep` etc.

Note that `\bibliographystyle` command should *not* be issued by the author: the package takes care of this. You just need to type

```
\bibliography{DATABASE, DATABASE...}
```

The bibliography style used for the articles is **resphilosophica.bst**. Compared to standard styles it has two additional fields:

doi: DOI number of the publication. Write there only the number: the style will automatically add <https://doi.org> and make the reference clickable.

titlenote: the note that should be put after the title rather than at the end of the entry¹, for example, the information about translators, editors of critical editions, etc:

```
@book{Knuth94:TheTeXbook,
  address =      {Reading, MA},
  author =      {Knuth, Donald Ervin},
  titlenote =    {Illustrations by Duane Bibby},
```

¹This field was proposed by Maureen Shupsky for the *Annals of Mathematics* bibliography style.

```

publisher = {Addison-Wesley Publishing Company},
series = {Computers \& Typesetting A},
title = {The \TeX book},
year = {1994},
}

```

`\enquote` The macros `\enquote` and `\ensquote` put their arguments in double and single
`\ensquote` quotes correspondingly. They are used to suppress unwanted commas and periods
inside bibliography entries.

`\suppresscomma` Sometimes Bib_{TEX} inserts an unwanted comma into an entry, for example, in
the following one:

```

@incollection{ande97a,
  Address = {Macon, GA},
  Author = {Anderson, Thomas C.},
  Booktitle = {Concluding Unscientific Postscript to
\enquote{Philosophical Fragments,}},
  Date-Modified = {2013-09-04 21:27:17 +0000},
  Editor = {Robert Perkins},
  Owner = {Andrew},
  Pages = {187--204},
  Publisher = {Mercer University Press},
  Series = {International Kierkegaard Commentary},
  Timestamp = {2013.09.04},
  Title = {Kierkegaard and Approximation Knowledge},
  Volume = {12},
  Year = {1997}}

```

The command `\suppresscomma` suppresses the next comma:

```

Booktitle = {Concluding Unscientific Postscript to
\enquote{Philosophical Fragments,\suppresscomma}},

```

The bibliography style has a special entry type, `inloosecollection`. It resembles the standard `incollection` entry, but it refers to a collection of papers written by separate authors that are quotable separately as an independent entity. This entry is typeset slightly differently than the standard `incollection` entry.

`\AddtoEndMatter` If you decide to forgo `natbib`, you can use `natbib=false` option. Then you should remember to put the bibliography *after* the end matter (authors' addresses etc) using the command `\AddtoEndMatter`:

```

\AddtoEndMatter{MY BIBLIOGRAPHY COMMANDS}

```

Acknowledgments

This package was commissioned by the journal *Res Philosophica* and funded by Saint Louis University. I am grateful to Jonathan Jacobs for tireless testing of the package.

4 Implementation

4.1 Options

We need `xkeyval` since some of our options may have values:

```
1 \RequirePackage{xkeyval}
```

`\ifRESP@fontauto` First, check whether the user have the body font explicitly configured:

```
2 \newif\ifRESP@fontauto
3 \RESP@fontautotruetrue
```

`\ifRESP@rpfontauto` Same for *Res Philosophica* font

```
4 \newif\ifRESP@rpfontauto
5 \RESP@rpfontautotruetrue
```

`\ifRESP@lsabon` Are we using linotype sabon?

```
6 \newif\ifRESP@lsabon
7 \RESP@lsabonfalse
```

`\ifRESP@mtshadow` Are we using MT Imprint Shadow?

```
8 %\newif\ifRESP@mtshadow
9 %\RESP@mtshadowfalse
```

`bodyfont` And the option to check the user input:

```
10 \define@choicekey*+{resphilosophica.cls}{bodyfont}[\val\nr]{auto,
11   sabon, lsabon, cm}[auto]{%
12   \ifcase\nr\relax
13     \RESP@fontautotruetrue
14   \or
15     \RESP@fontautofalse
16     \RESP@lsabontrue
17   \or
18     \RESP@fontautofalse
19     \RESP@lsabontrue
20   \or
21     \RESP@fontautofalse
22     \RESP@lsabonfalse
23   \fi}{%
24   \PackageWarning{resphilosophica}{The option bodyfont must be auto,
25     sabon or cm. Using auto}\RESP@fontautotruetrue}
```

`rpfont` And the option to check the user input:

```
26 % \define@choicekey*+{resphilosophica.cls}{rpfont}[\val\nr]{auto,
27 %   imprint, imprintshadow, cm}[auto]{%
28 %   \ifcase\nr\relax
29 %     \RESP@rpfontautotruetrue
30 %   \or
31 %     \RESP@rpfontautofalse
32 %     \RESP@mtshadowtrue
33 %   \or
34 %     \RESP@rpfontautofalse
35 %     \RESP@mtshadowtrue
36 %   \or
```

```

37 % \RESP@rpfontautofalse
38 % \RESP@mtshadowfalse
39 % \fi}{%
40 % \PackageWarning{resphilosophica}{The option rpfont must be auto,
41 % imprintshadow or cm. Using auto}\RESP@rpfontautottrue}

```

natbib Checking natbib option:

```

42 \define@boolkey+{resphilosophica.cls}[RESP@]{natbib}[true]{}{%
43 \PackageWarning{resphilosophica}{The option natbib must be
44 yes or no. Using yes}}
45 \RESP@natbibtrue

```

The size-changing options produce a warning:

```

46 \long\def\RESP@size@warning#1{%
47 \ClassWarning{RESPart}{Size-changing option #1 will not be
48 honored}}%
49 \DeclareOptionX{8pt}{\RESP@size@warning{\CurrentOption}}%
50 \DeclareOptionX{9pt}{\RESP@size@warning{\CurrentOption}}%
51 \DeclareOptionX{10pt}{\RESP@size@warning{\CurrentOption}}%
52 \DeclareOptionX{11pt}{\RESP@size@warning{\CurrentOption}}%
53 \DeclareOptionX{12pt}{\RESP@size@warning{\CurrentOption}}%

```

\ifRESP@manuscript Manuscript mode:

```

54 \newif\ifRESP@manuscript
55 \RESP@manuscriptfalse
56 \DeclareOptionX{manuscript}{\RESP@manuscripttrue}

```

\ifRESP@screen Screen mode:

```

57 \newif\ifRESP@screen
58 \RESP@screenfalse
59 \DeclareOptionX{screen}{\RESP@screentrue}

```

\ifRESP@preprint Whether we are in the preprint mode

```

60 \newif\ifRESP@preprint
61 \RESP@preprintfalse
62 \DeclareOptionX{preprint}{\RESP@preprinttrue}

```

\ifRESP@forthcoming Whether we are in the forthcoming mode

```

63 \newif\ifRESP@forthcoming
64 \RESP@forthcomingfalse
65 \DeclareOptionX{forthcoming}{\RESP@forthcomingtrue}

```

All other options are passed to amsart:

```

66 \DeclareOptionX{*}{\PassOptionsToClass{\CurrentOption}{amsart}}

```

And executing options:

```

67 \ProcessOptionsX

```

4.2 Loading Classes and Packages

We use amsart since it has nice features for front matter:

```

68 \LoadClass[noamsfonts,twoside]{amsart}

```

Some packages

```

69 \RequirePackage{microtype, fancyhdr, xcolor, collect}
70 \RequirePackage[bottom,multiple]{footmisc}
71 \PassOptionsToPackage{hyphens}{url}
72 \RequirePackage[hyperfootnotes=false]{hyperref}
73 \urlstyle{rm}
74 \ifRESP@manuscript\hypersetup{colorlinks,allcolors=blue}\else
75   \ifRESP@screen\hypersetup{colorlinks,allcolors=blue}\else
76     \ifRESP@preprint\hypersetup{colorlinks,allcolors=blue}\else
77       \ifRESP@forthcoming\hypersetup{colorlinks,allcolors=blue}\else
78         \hypersetup{hidelinks}\fi\fi\fi\fi

```

The font to use depends on the options. Note that $\text{\LaTeX}$ cannot reliably determine whether a binary file like `SabonLTRom.pfb` exists in the system, so we check for the `.fd` file instead (sigh):

```

79 \ifRESP@fontauto
80   \IfFileExists{t1lsb.fd}{\RESP@lsabontrue}{\RESP@lsabonfalse}\fi

```

If the user wants, we load Sabon and URW Garamond. Note that `mathdesign` defines `sc` to be `fsc`, so we need to redefine it for Sabon. Also, it defines `b` to `mb`, so we redefine it again.

```

81 \ifRESP@lsabon
82   \RequirePackage[mdugm]{mathdesign}
83   \RequirePackage[rmdefault]{lsabon}
84   \renewcommand\scdefault{sc}
85   \renewcommand{\bfdefault}{b}
86 \fi

```

Checking the existence of `miih` font metrics:

```

87 %\ifRESP@rpfontauto
88 % \IfFileExists{t1miih.fd}{\RESP@mtshadowtrue}{\RESP@mtshadowfalse}\fi

```

`\rpdefault` This is the font for *Res Philosophica*:

```

89 %\ifRESP@mtshadow
90 % \def\rpdefault{miih}\else
91 % \def\rpdefault{\rmdefault}\fi

```

`\AddtoEndMatter` A syntax sugar to add something after signature:

```

92 \def\AddtoEndMatter#1{\g@addto@macro\enddoc@text{#1}}

```

And loading `natbib`:

```

93 \ifRESP@natbib
94   \RequirePackage[round]{natbib}
95   \AtEndDocument{\bibliographystyle{resphilosophica}}
96   \let\RESP@bibliography=\bibliography
97   \def\bibliography#1{\AddtoEndMatter{\RESP@bibliography{#1}}}
98   \def\bibsection{\par\addpenalty\@secpenalty\addvspace{\bigskipamount}%
99     \noindent \Small References:\par\nobreak\vskip\medskipamount\@afterheading}
100   \def\bibfont{\Small}
101 \fi

```

4.3 Page Dimensions and Paragraphing

`\pdfpaperwidth` Paper:
`\pdfpaperheight` 102 `\ifRESP@manuscript\else`
103 `\AtBeginDocument{\setlength{\pdfpagewidth}{432bp}%`
104 `\setlength{\pdfpageheight}{648bp}}`
105 `\fi`

`\textwidth` The size of the type block:
`\textheight` 106 `\setlength{\textwidth}{318pt}`
107 `\setlength{\textheight}{540pt}`

`\evensidemargin` The margins:
`\oddsidemargin` 108 `\setlength{\evensidemargin}{-0.125in}`
109 `\setlength{\oddsidemargin}{-0.25in}`
110 `\ifRESP@screen`
111 `\setlength{\evensidemargin}{-0.1875in}`
112 `\setlength{\oddsidemargin}{-0.1875in}`
113 `\fi`
114 `\ifRESP@forthcoming`
115 `\setlength{\evensidemargin}{-0.1875in}`
116 `\setlength{\oddsidemargin}{-0.1875in}`
117 `\fi`

`\topmargin` Top margin
118 `\setlength{\topmargin}{-48pt}`

`\listisep` This is the space around lists. `amsart` defines it as `\smallskipamount`. We slightly increase it:
119 `\listisep\medskipamount`

4.4 Headers

`\headsep` Separation between the header and the body
120 `\setlength{\headsep}{14pt}`

`\headheight` The height of the headers:
121 `\setlength{\headheight}{12pt}`

`\headrulewidth` We do not want decorative rules in the journal:
`\footrulewidth` 122 `\renewcommand{\headrulewidth}{0pt}`
123 `\renewcommand{\footrulewidth}{0pt}`

`\footskip` Separation between the footer and the body
124 `\setlength{\footskip}{20pt}`

`\RESP@printlinecount` Do we want to print line count?
125 `\newif\ifRESP@printlinecount`
126 `\RESP@printlinecountfalse`
127 `\ifRESP@manuscript\RESP@printlinecounttrue\fi`
128 `\ifRESP@preprint\RESP@printlinecounttrue\fi`

\RESP@linecount This is the box displayed in the manuscript mode

```

129 \ifRESP@printlinecount
130   \newsavebox{\RESP@linecount}
131   \savebox{\RESP@linecount}[4em][t]{\parbox[t]{4em}{%
132     \@tempcnta\@ne\relax
133     \loop{\color{red}\scriptsize\the\@tempcnta}\
134       \advance\@tempcnta by \@ne\ifnum\@tempcnta<47\repeat}}
135 \fi

```

It is easy to set up headers with fancyhdr:

```

136 \pagestyle{fancy}
137 \fancyhead{}
138 \fancyfoot{}
139 \fancyhead[LE]{\footnotesize\thepage\quad\itshape\shortauthors}
140 \fancyhead[RO]{\footnotesize\textit{\shorttitle}\quad\thepage}
141 \ifRESP@printlinecount
142   \fancyhead[LE]{\begin{picture}(0,0)%
143     \put(-26,-22){\usebox{\RESP@linecount}}%
144     \end{picture}\footnotesize\thepage\quad\itshape\shortauthors}
145   \fancyhead[LO]{\begin{picture}(0,0)%
146     \put(-21,-22){\usebox{\RESP@linecount}}%
147     \end{picture}}
148 \fi
149 \ifRESP@manuscript
150   \fancyfoot[C]{\scriptsize\color{red}Author's Proof}%
151 \fi
152 \ifRESP@preprint
153   \fancyfoot[C]{\scriptsize\color{red}Author's Pre-Print}%
154 \fi

```

The first page has the special headers. The style `firstpage` is invoked by `amsart`; here we just redefine it.

```

155 \fancypagestyle{firstpage}{%
156   \fancyhf{}%
157   \ifRESP@printlinecount
158     \lhead{\begin{picture}(0,0)%
159       \put(-26,-20){\usebox{\RESP@linecount}}%
160       \end{picture}}
161   \fi
162   \ifRESP@preprint
163     \cfoot{\footnotesize Res Philosophica, \itshape
164       Vol.~\currentvolume, No.~\currentissue,
165       \currentmonth~\currentyear
166       \ifx\@doinumber\@empty\else\\%
167       \doi{\@doinumber}\fi
168       \\
169       \@copyrightnote}%
170     \chead{\scriptsize\color{red}Author's Pre-print. Forthcoming in
171       Res Philosophica. Pagination may change. Published version will
172       be available at \url{http://pdcnet.org/resphilosophica/}}
173   \else
174     \ifRESP@forthcoming
175       \cfoot{\footnotesize Res
176         Philosophica\itshape

```

```

177 \ifx\currentvolume\@empty\else, %
178 Vol.\currentvolume\fi
179 \ifx\currentissue\@empty\else, No.\currentissue\fi
180 \ifx\currentmonth\@empty
181 \ifx\currentyear\@empty\else, \currentyear\fi
182 \else,
183 \currentmonth\currentyear
184 \fi
185 \ifx\@doinumber\@empty\else\%
186 \doi{\@doinumber}\fi
187 \\
188 \@copyrightnote}%
189 \head{\raisebox{1.5\bigskipamount}[\z@][\z@]{\parbox{\textwidth}{\raggedright\footnotesize
190 \else
191 \cfoot{\footnotesize Res Philosophica, \itshape
192 \itshape Vol.\currentvolume, No.\currentissue,
193 \currentmonth\currentyear, pp.\start@page--\end@page
194 \ifx\@doinumber\@empty\else\%
195 \doi{\@doinumber}\fi
196 \\
197 \@copyrightnote}%
198 \fi\fi}

```

4.5 Top Matter Macros

Most top matter macros are defined in `amsart`. Here we just add some new macros and redefine some.

The next macros mimic the functionality of `amsart \issueinfo` command. Note that `\issueinfo` still works.

`\volumenumber` This sets the volume of the paper

```

199 \def\volumenumber#1{\def\currentvolume{#1}}
200 \volumenumber{}

```

`\issuenummer` This sets the issue of the paper:

```

201 \def\issuenummer#1{\def\currentissue{#1}}
202 \issuenummer{}

```

`\publicationyear` This sets the year of the paper

```

203 \def\publicationyear#1{\def\currentyear{#1}}
204 \publicationyear{}

```

`\publicationmonth` This sets the month of the paper

```

205 \newcommand\publicationmonth[2][\gdef\currentmonth{#2}%
206 \gdef\abbrevcurrentmonth{#1}%
207 \ifx\abbrevcurrentmonth\@empty\gdef\abbrevcurrentmonth{#2}\fi}
208 \publicationmonth{}

```

`\papernumber` This is absent from the `\issueinfo`.

```

209 \def\papernumber#1{\def\currentpaper{#1}}
210 \papernumber{0000}
211 %
212 % \end{macro}

```

```

213 %
214 % \begin{macro}{\manuscriptid}
215 % \changes{v1.29}{2016/08/26}{Added macro}
216 %   Submission id
217 %   \begin{macrocode}
218 \def\manuscriptid#1{\gdef\@manuscriptid{#1}}
219 \manuscriptid{}
220 %
221 % \end{macro}
222 %
223 %
224 % \begin{macro}{\doinumber}
225 % \changes{v1.11}{2012/12/25}{Added default}
226 % \changes{v1.29}{2016/08/26}{Now we use \cs{manuscriptid} to make
227 % doi}
228 % \changes{v1.40}{2026/08/10}{New doi prefix}
229 %   DOI number for the article:
230 %   \begin{macrocode}
231 \def\doinumber#1{\gdef\@doinumber{#1}}
232 \doinumber{\ifx\@manuscriptid\empty
233   10.5840/resphil.\currentyear.\currentvolume.\currentissue.\currentpaper
234   \else
235   10.5840/resphil.\@manuscriptid
236   \fi}

\paperUrl The url to submit to crossref
237 \def\paperUrl#1{\gdef\@paperUrl{#1}}
238 \paperUrl{}

\startpage This defines the starting page of the paper. We have some nice features to set up
roman page numbers for editorial stuff—probably not needed for this journal at
this time...
239 \def\startpage#1{\pagenumbering{arabic}\setcounter{page}{#1}%
240   \def\start@page{#1}%
241   \ifnum\c@page<\z@ \pagenumbering{roman}\setcounter{page}{-#1}%
242   \def\start@page{\romannumeral#1}%
243   \fi}

\endpage This macro again has a twist in it: if the argument is not set, it calculates the last
page number itself.
244 \def\endpage#1{\def\@tempa{#1}%
245   \ifx\@tempa\empty\def\end@page{\pageref{RP@LastPage}}%
246   \else\def\end@page{#1}\fi}

\pagespan This macro is different from the one provided by amsart because we want to have
the option of automatic calculation of the last page number.
247 \def\pagespan#1#2{\startpage{#1}\endpage{#2}}
248 \pagespan{1}{}

\articleentry This is necessary for \prevpaper command. We read the TOC entry from the
previous paper and increment it by 1. Note that we always start with on an odd
page, since the additional check
249 \def\articleentry#1#2#3#4{\@tempcnta=#4\relax

```

```

250 \advance\@tempcnta by 1\relax
251 \ifodd\the\@tempcnta\else\advance\@tempcnta by 1\relax\fi
252 \startpage{\the\@tempcnta}}

```

`\prevpaper` This sets the previous paper location and reads the information from the previous paper

```

253 \def\prevpaper#1{\IfFileExists{#1.rpi}{%
254   \ClassInfo{resphilosophica}{%
255     Reading first page number from the file #1.rpi}%
256   \input{#1.rpi}%
257 }{\ClassWarning{resphilosophica}{Cannot find the file #1.rpi.
258   Did you run latex on the previous paper?}}}

```

`abstract` We slightly redefine abstract comparing to amsart conventions:

```

259 \renewenvironment{abstract}{%
260   \ifx\maketitle\relax
261     \ClassWarning{resphilosophica}{Abstract should precede
262       \protect\maketitle\space in AMS derived classes}%
263   \fi
264   \global\setbox\abstractbox=\vtop\bgroup%
265   \vglue1pc%
266   \list{}{\labelwidth\z@%
267     \leftmargin3pc \rightmargin\leftmargin%
268     \listparindent\normalparindent \itemindent\z@%
269     \parsep\z@ \@plus\p@%
270     \let\fullwidthdisplay\relax%
271   }%
272   \item[]\normalfont\normalsize\textbf{\abstractname:}\space
273 }{%
274   \endlist\egroup%
275   \ifx\@setabstract\relax\@setabstracta\fi%
276 }

```

`\copyrightyear` This is the copyright year in case it does not coincide with the publication year:

```

277 \def\copyrightyear#1{\def\@copyrightyear{#1}}
278 \ifRESP@forthcoming
279   \copyrightyear{\the\year}\else
280   \copyrightyear{}\fi

```

`\onlinedate` Online date for forthcoming issues

```

\@onlinedate 281 \def\onlinedate#1{\gdef\@onlinedate{#1}}
282 \onlinedate{\hspace*{5em}}

```

`\RESP@bulletboxwidth` This is the width of a box with a bullet for copyright note:

```

283 \newlength\RESP@bulletboxwidth
284 \settowidth\RESP@bulletboxwidth{\quad\textbullet\quad}

```

`\copyrightnote` This is the copyrightnote. The default has some trickery with the year and short authors.

The disappearing bullet is based on the trick by Marcin Wolinński, who noted that `\cleaders` are discardable (see [4]).

```

285 \def\copyrightnote#1{\def\@copyrightnote{#1}}
286 \copyrightnote{\textcopyright~%

```

```

287 \ifx\@empty\@copyrightyear\currentyear\else\@copyrightyear\fi~%
288 \shortauthors\cleaders\hbox{\quad\textbullet\quad}\hskip\RESP@bulletboxwidth
289 \textcopyright~%
290 \ifx\@empty\@copyrightyear\currentyear\else\@copyrightyear\fi~%
291 {\upshape Res~Philosophica}}%

```

`\author` This base class puts into `\addresses` the strange line `\author{}`. We correct this:

```

292 \renewcommand{\author}[2][]{%
293   \ifx\@empty\addresses
294     \gdef\addresses{\author{#2}}%
295   \else
296     \g@addto@macro\addresses{\author{#2}}%
297   \fi
298   \ifx\@empty\authors
299     \gdef\authors{#2}%
300   \else
301     \g@addto@macro\authors{\and#2}%
302   \fi
303   \@ifnotempty{#1}{%
304     \ifx\@empty\shortauthors
305       \gdef\shortauthors{#1}%
306     \else
307       \g@addto@macro\shortauthors{\and#1}%
308     \fi
309   }%
310 }
311 \edef\author{\@nx\@dblarg
312   \@xp\@nx\csname\string\author\endcsname}

```

`\titlenote` This command adds an entry to the list of titlenotes

```

313 \def\@titlenotes{}%
314 \def\titlenote#1{%
315   \ifx\@empty\@titlenotes\gdef\@titlenotes{\footnote{#1}}%
316   \else\g@addto@macro\@titlenotes{\footnote{#1}}\fi}

```

`\authornote` This command adds an entry to the list of titlenotes

```

317 \def\@authornotes{}%
318 \def\authornote#1{%
319   \ifx\@empty\@authornotes\gdef\@authornotes{\footnote{#1}}%
320   \else\g@addto@macro\@authornotes{\footnote{#1}}\fi}

```

4.6 Typesetting Top Matter

`\@settitle` We do not uppercase title. Also, we use this occasion to set PDF information:

```

321 \def\@settitle{\begin{center}%
322   \baselineskip20\p@\relax
323   \LARGE\scshape
324   \renewcommand\thefootnote{\@fnsymbol\c@footnote}%
325   \ifx\itscshape\@undefined\else\def\em{\itscshape}\fi
326   \@title\@titlenotes
327   \hypersetup{pdftitle=\@title}%
328   \end{center}%
329 }

```

`\@setauthors` Now we typeset authors according to our specs. Again, we use this occasion to set some PDF information:

```

330 \def\@setauthors{%
331   \ifx\authors\@empty\relax\else
332     \begingroup
333     \def\thanks{\protect\thanks@warning}%
334     \trivlist
335     \centering\footnotesize \@topsep30p\relax
336     \advance\@topsep by -\baselineskip
337     \item\relax
338     \def\@and{{and}}
339     \author@andify\authors
340     \hypersetup{pdfauthor=\authors}%
341     \def\{\{\protect\linebreak\}%
342     \renewcommand\thefootnote{\@fnsymbol\c@footnote}%
343     \large\normalfont\authors\@authornotes
344     \endtrivlist
345     \endgroup
346   \fi}

```

`\maketitle` We redefine `\maketitle`—mostly to prevent uppercasing of shorttitle and to write down the journal information:

```

347 \def\maketitle{\par
348   \@topnum\z@ % this prevents figures from falling at the top of page 1
349   \@setcopyright
350   \thispagestyle{firstpage}% this sets first page specifications
351   \ifx\@empty\shortauthors \let\shortauthors\shorttitle
352   \else \andify\shortauthors
353   \fi
354   \@maketitle@hook
355   \RESP@write@paper@info
356   \begingroup
357   \@maketitle
358   \toks@{\xp{\shortauthors}}\@temptokena{\xp{\shorttitle}}%
359   \toks4{\def\{\ \ignorespaces}}% defend against questionable usage
360   \edef\@tempa{%
361     \nx\markboth{\the\toks4
362       \nx\MakeUppercase{\the\toks@}}{\the\@temptokena}}%
363   \@tempa
364   \endgroup
365   \c@footnote\z@
366   \everypar{\setbox\z@\lastbox\everypar{}}%
367 }

```

`\@maketitle` We delete top space introduced by `amsart`:

```

368 \def\@maketitle{%
369   \normalfont\normalsize
370   \@adminfootnotes
371   \@mkboth{\nx\shortauthors}{\nx\shorttitle}%
372   \@settitle
373   \ifx\@empty\authors \else \@setauthors \fi
374   \ifx\@empty\@dedicatory
375   \else
376     \baselineskip18p@

```

```

377 \vtop{\centering{\footnotesize\itshape\@dedicatory\@par}%
378 \global\dimen@i\prevdepth}\prevdepth\dimen@i
379 \fi
380 \@setabstract
381 \normalsize
382 \if@titlepage
383 \newpage
384 \else
385 \dimen@34\p@ \advance\dimen@-\baselineskip
386 \vskip\dimen@\relax
387 \fi
388 } % end \@maketitle

```

\@mainrpi The stream for the rpi file:

```

389 \newwrite\@mainrpi

```

\RESP@write@paper@info This writes the information about the paper into the file jobname.rpi. Note that hyperref makes our life a little bit more complex

```

390 \def\RESP@write@paper@info{%
391 \bgroup
392 \if@filesw
393 \openout\@mainrpi\jobname.rpi%
394 \write\@mainrpi{\relax}%
395 \ifx\r@RP@LastPage\@undefined
396 \edef\@tempa{\start@page}%
397 \else
398 \def\@tempc##1##2##3##4##5{##2}%
399 \edef\@tempa{\expandafter\@tempc\r@RP@LastPage}%
400 \fi
401 \def\and{\string\and\space}%
402 \protected@write\@mainrpi{%
403 {\string\articleentry{\authors}{\@title}{\start@page}{\@tempa}}%

```

The next lines are for crossref software

```

404 \protected@write\@mainrpi{%
405 {\@percentchar authors=\authors}%
406 \protected@write\@mainrpi{%
407 {\@percentchar title=\@title}%
408 \protected@write\@mainrpi{%
409 {\@percentchar year=\currentyear}%
410 \protected@write\@mainrpi{%
411 {\@percentchar volume=\currentvolume}%
412 \protected@write\@mainrpi{%
413 {\@percentchar issue=\currentissue}%
414 \protected@write\@mainrpi{%
415 {\@percentchar paper=\currentpaper}%
416 \protected@write\@mainrpi{%
417 {\@percentchar startpage=\start@page}%
418 \protected@write\@mainrpi{%
419 {\@percentchar endpage=\@tempa}%
420 \protected@write\@mainrpi{%
421 {\@percentchar doi=\@doinumber}%
422 \ifx\@paperUrl\@empty\else
423 \protected@write\@mainrpi{%

```

```

424     {\@percentchar paperUrl=\@paperUrl}%
425     \fi
426     \closeout\@mainrpi
427     \fi
428 \egroup}

\@adminfootnotes We just define this to noop:
429 \def\@adminfootnotes{}

\@cleartopmattertags We typeset thankses at the end of the paper so we do not clear them:
430 \def\@cleartopmattertags{%
431   \def\do##1{\let##1\relax}%
432   \do\maketitle \do\@maketitle \do\title \do\@xtitle \do\@title
433   \do\author \do\@xauthor \do\address \do\@xaddress
434   \do\contrib \do\contribs \do\@xcontribs \do\tocontribs
435   \do\email \do\@xemail \do\curraddr \do\@xcurraddr
436   \do\commby \do\@commby
437   \do\dedicatory \do\@dedicatory \do\thanks
438   \do\keywords \do\@keywords \do\subjclass \do\@subjclass

\sffsize It seems there is a bug in mdugm when calculating \sf@size. Here we work around
it:
439   \def\sffsize{7}%
440 }
```

4.7 Notes

```

\notes This is like bibliography:
441 \definecollection{notes}
442 \newenvironment{notes}[1]{%
443   \@nameuse{collect}{notes}{-}{-}%
444   \makeatletter
445   \par\addpenalty\@secpenalty\addvspace{\bigskipamount}%
446   \noindent \Small #1:\par\nobreak\vskip\medskipamount\@afterheading
447   \makeatother
448 }{\@nameuse{endcollect}\AddtoEndMatter{\includecollection{notes}}}
```

4.8 Typesetting End Matter

End matter is typeset at the end of the paper.

```

\if@enddoc Check whether we are in the end matter
449 \newif\if@enddoc
450 \@enddocfalse

\enddoc@text We put thankses into end matter. Also, we redefine bibliography back to the
original definition in case someone writes \AddtoEndMatter{\bibliography{}}
451 \def\enddoc@text{%
452   \@enddoctrue\def\bibliography{\RESP@bibliography}%
453   \ifx\@empty\thankses\else
454     \bgroup
455     \let\@makefnmark\relax
456     \let\@thefnmark\relax
```

Check, whether we are at the same page as the last footnote; if yes, add medskip.

```

457 \ifx\lastfootnote@page\@undefined\else
458     \@tempcnta=\lastfootnote@page\relax
459     \ifnum\c@page=\@tempcnta\relax
460         \insert\footins{\medskip}%
461     \fi
462 \fi

463 \@footnotetext{%
464     \def\par{\let\par\@par}\textbf{Acknowledgments\quad} \setthanks}%
465 \egroup
466 \fi
467 \ifx\@empty\@translators \else\@settranslators\fi
468 \ifx\@empty\addresses \else\@setaddresses\fi

```

\ifRESP@firstingroup A group of authors is separated by a skip from another group. This macro checks whether this is the first one

```

469 \newif\ifRESP@firstingroup

```

\emailaddrname The name for e-mail address:

```

470 \def\emailaddrname{E-mail}

```

\@setaddresses Unlike `aomart`, we want to preserve author's name in the address block. Also, we want to keep linebreaks and to have clickable e-mail and URL.

We want to skip between the author groups (several authors with the same affiliation), so we check whether the previous line contains another author:

```

471 \def\@setaddresses{\par
472     \nobreak \begingroup\flushright\clubpenalty\@MM\interlinepenalty\@MM
473     \widowpenalty\@MM
474     \RESP@firstingrouptrue
475 \Small
476     \def\author##1{\nobreak\ifRESP@firstingroup\par
477         \addvspace\bigskipamount\penalty-1000\fi
478         \RESP@firstingroupfalse##1\par\nobreak}%
479     \parindent\z@
480     \def\address##1##2{\RESP@firstingrouptrue\begingroup
481         \par\nobreak
482         \@ifnotempty{##1}{(\ignorespaces##1\unskip) }%
483         {\ignorespaces##2}\par\endgroup}%
484     \def\curraddr##1##2{\RESP@firstingrouptrue\begingroup
485         \@ifnotempty{##2}{\nobreak\indent\curraddrname
486             \@ifnotempty{##1}{, \ignorespaces##1\unskip}:\space
487             ##2\par}\endgroup}%
488     \def\email##1##2{\RESP@firstingrouptrue\begingroup
489         \@ifnotempty{##2}{\nobreak\indent\emailaddrname
490             \@ifnotempty{##1}{, \ignorespaces##1\unskip}:\space
491             \href{mailto:##2}{\nolinkurl{##2}}\par}\endgroup}%
492     \def\urladdr##1##2{\RESP@firstingrouptrue\begingroup
493         \@ifnotempty{##2}{\nobreak\indent
494             \@ifnotempty{##1}{, \ignorespaces##1\unskip}%
495             \url{##2}\par}\endgroup}%
496     \addresses
497 \endgroup
498 }

```

At the end we eject the last page. If the document is printed and the last page is odd, we add an empty page. It is not counted in the `RP@LastPage` count. We use code from `lastpage` package

```

499 \AtEndDocument{\clearpage
500   \begingroup%
501     \addtocounter{page}{-1}%
502     \def\Hy@temp{\arabic{page}}%
503     \immediate\write\@auxout{%
504       \string\newlabel{RP@LastPage}{\thepage}{\thepage}{\thepage}{\thepage}%
505       \ifHy@pageanchor page.\Hy@temp\fi}{}}%
506   }%
507   \addtocounter{page}{+1}%
508 \endgroup%
509 \ifRESP@manuscript\else
510 \ifRESP@screen\else
511 \ifRESP@preprint\else
512 \ifRESP@forthcoming\else
513 \cleardoublepage
514 \fi\fi\fi\fi}

```

4.9 Sectioning

`\@secntformat` We do not want our numbers to be upright and medium series, as `amsart` wants:

```

515 \def\@secntformat#1{%
516   \csname the#1\endcsname\enspace
517 }

```

`\section` We want our sections to be large and bold:

```

518 \renewcommand\section{\@startsection {section}{1}{\z@}%
519                                     {-3.5ex \@plus -1ex \@minus -.2ex}%
520                                     {2.3ex \@plus .2ex}%
521                                     {\normalfont\large\bfseries}}

```

`\subsection` Subsections are bold

```

522 \renewcommand\subsection{\@startsection{subsection}{2}{\z@}%
523                                     {-3.25ex \@plus -1ex \@minus -.2ex}%
524                                     {1.5ex \@plus .2ex}%
525                                     {\normalfont\normalsize\bfseries}}

```

`\subsubsection` Subsubsections are normalsize and italic

```

526 \renewcommand\subsubsection{\@startsection{subsubsection}{3}{\z@}%
527                                     {-3.25ex \@plus -1ex \@minus -.2ex}%
528                                     {1.5ex \@plus .2ex}%
529                                     {\normalfont\normalsize\itshape}}

```

`\paragraph` Paragraphs:

```

530 \renewcommand\paragraph{\@startsection{paragraph}{4}{\z@}%
531                                     {3.25ex \@plus 1ex \@minus .2ex}%
532                                     {-1em}%
533                                     {\normalfont\normalsize\bfseries}}

```

`\subparagraph` Paragraphs:

```

534 \renewcommand\subparagraph{\@startsection{subparagraph}{5}{\parindent}%
535                                     {3.25ex \@plus1ex \@minus .2ex}%
536                                     {-1em}%
537                                     {\normalfont\normalsize\bfseries}}

```

4.10 Additional Commands

`\@mparswitch` We always put marginpars on the right since the line box is on the left

```
538 \@mparswitchfalse
```

`\EditorialComment` This macro is noop in normal mode, but is a tiny marginpar in the manuscript mode

```

539 \newcommand\EditorialComment[2][0]{%
540   \expandafter\ifx\csname EditorialComment@#1\endcsname\relax
541   \else\bgroup
542   \marginparwidth=200pt\marginpar{\color{red}%
543     \raggedright#2}\egroup\fi}

```

`\ECSelect` This selects the given levels

```

544 \def\ECSelect#1{\ifRESP@manuscript
545   \@for\EC@level:=#1\do{%
546     \expandafter\gdef\csname
547       EditorialComment@\EC@level\endcsname{\EditorialComment}}%
548   \fi}

```

`\TC` The command to highlight text if the corresponding level is selected. The first argument is the level, the second is text.

```

549 \newcommand\TC[2][0]{%
550   \expandafter\ifx\csname TC@highlight@#1\endcsname\relax#2\else
551   \csname TC@highlight@#1\endcsname{#2}\fi}

```

`\TCSelect` This switches on the selected levels in the manuscript version

```

552 \newcommand\TCSelect[2][magenta]{\ifRESP@manuscript
553   \@for\TC@level:=#2\do{\expandafter
554     \gdef\csname TC@highlight@\TC@level\endcsname##1{\bgroup
555       \Hy@colorlinksfalse
556       \def\Hy@colorlink####1{\begingroup}%
557       \def\Hy@endcolorlink{\endgroup}%
558       \color{#1}##1\egroup}}%
559   \fi}

```

`\doi` Typesetting doi...

```
560 \def\doi#1{\url{https://doi.org/#1}}
```

`\@makefnmark` The definition of `\@makefnmark` in `amsart` has a bug. Here we return to the L^AT_EX one:

```
561 \def\@makefnmark{\hbox{\@textsuperscript{\normalfont\@thefnmark}}}
```

`\@makefntext` Unlike `amsart`, we do not indent footnotes:

```

562 \def\@makefntext{\noindent\@makefnmark
563   \if@enddoc\else
564   \immediate\write\@mainaux%

```

```

565     {\string\xdef\string\lastfootnote@page{\the\c@page}}%
566     \fi}
567 \long\def\@footnotetext#1{%
568     \insert\footins{%
569         \normalfont\footnotesize
570         \interlinepenalty\interfootnotelinepenalty
571         \splittopskip\footnotesep \splitmaxdepth \dp\strutbox
572         \floatingpenalty\@MM \hsize\columnwidth
573         \@parboxrestore \parindent\normalparindent \sloppy
574         \protected@edef\@currentlabel{%
575             \csname p@footnote\endcsname\@thefnmark}%
576         \@makefntext{%
577             \,\rule\z@\footnotesep\ignorespaces#1\unskip\strut\par}}}

```

4.11 The End

Philosophers love footnotes, since `\raggedbottom`

```

578 \raggedbottom\normalsize\normalfont
579 </class>

```

References

- [1] Boris Veytsman. *Support files for the Linotype Sabon Fonts*, August 2015. <http://mirrors.ctan.org/fonts/l sabon/>.
- [2] Patrick W. Daly. *Natural Sciences Citations and References (Author-Year and Numerical Schemes)*, February 2009. <http://mirrors.ctan.org/macros/latex/contrib/natbib>.
- [3] American Mathematical Society. *Instructions for Preparation of Papers and Monographs, AMS $\LaTeX$* , August 2004. <http://mirrors.ctan.org/macros/latex/required/amslatex/classes/instr-1.pdf>.
- [4] Paweł Jackowski. $\TeX$ beauties and oddities. *TUGboat*, 29:207–215, 2008. <http://www.tug.org/TUGboat/tb29-1/tb91pearls.pdf>.

Change History

v1.1	General: Added DOI number 1	\volumenumber: The default is now empty 13
	Added MT Shadow Imprint code 1	
	\@maketitle: Redefined macro . . 17	v1.14 \sf@size: Bug corrected 19
	\@mparswitch: Changed default . . 22	v1.15
	\@setauthors: Changed font . . . 17	General: Added new bibliography command 1
	\doi: Added macro 22	v1.16
	\EditorialComment: Added macro 22	General: Added \bfdefault 10
	\ifRESP@mtshadow: Added macro . 8	Added documentation about typesetter changes highlighting 1
	\ifRESP@rpfontauto: Added macro 8	Deleted Imprint Shadow 1
	rpfont: Added option 8	\@makefntext: Added small space after footnote mark 22
	\RESP@write@paper@info: Added protection for \ 18	\@onlinedate: Added macro . . . 15
	\rpdefault: Added macro 10	\copyrightnote: Deleted rpdefault 15
	\section: Moved to LaTeX defaults 21	\ifRESP@mtshadow: Deleted macro 8
	\subsection: Moved to LaTeX defaults 21	\maketitle: Added suppressing first para indentation 17
	\subsubsection: Moved to LaTeX defaults 21	\notes: Added macro 19
v1.10	General: Bibliography changes . . . 1	\onlinedate: Added macro 15
v1.11	General: Bibliography changes . . . 1	rpfont: Deleted option 8
	\papernumber: Added macro . . . 13	\publicationmonth: Added \abbrevcurrentmonth 13
	\RESP@write@paper@info: Added writing info for crossref 18	\rpdefault: Deleted macro 10
v1.12	General: Bibliography changes . . . 1	\TC: Added macro 22
v1.13	General: Changed check for line numbering mode 12	\TCSelect: Added macro 22
	New command: titlenote 1	v1.17
	New options: preprint and forthcoming 1	General: Added collect package . 10
	\@settitle: Added titlenotes . . . 16	Added documentation about new editorial comments 1
	\copyrightnote: Changed font family for forthcoming mode . 15	Bibliography changes: ‘inloosecollection’ entry 1
	\ifRESP@forthcoming: Added option 9	Journal name on the first page footer is now italic 12
	\ifRESP@preprint: Added option . 9	Online date for forthcoming option moved to the left and up 12
	\issuenumber: The default is now empty 13	\ECSelect: Added macro 22
	\publicationmonth: The default is now empty 13	\EditorialComment: Redefined so levels are supported 22
	\publicationyear: The default is now empty 13	\notes: Redefined using collect package 19
	\RESP@printlinecount: Added macro 11	v1.18
	\titlenote: Added command . . 16	General: Journal name in Roman 12
		Online date for forthcoming option moved down 12
		\copyrightnote: Made journal name Roman 15

v1.19	\TCSelect: Switched off colored links	22	v1.28	General: Now ensquote and enquote work correct in the case of embedded quotations . .	1
v1.2	General: Changed font for bibliography	10	v1.3	General: Added penalties	10
	Changed skip for bibliography	10		Ifpdf is no longer needed with modern engines	10
	\@adminfootnotes: Redefined	19		\@setaddresses: Added penalties	20
	\@cleartopmattertags: Redefined	19		\@setauthors: Deleted ifpdf	17
	\@setaddresses: Changed font	20		\@settitle: Deleted ifpdf	16
	\@setauthors: Changed font	17		\copyrightyear: In the forthcoming mode the copyright year is the present year	15
	\copyrightnote: Used \rpdefault for RP font	15		\pdfpaperheight: Deleted ifpdf	11
	\enddoc@text: Redefined	19		\RESP@linecount: Changed check for linecount	12
	\listisep: Redefined	11	v1.30	General: Split URLs at hyphens	10
	\RESP@write@paper@info: Used \protected@write	18	v1.31	\doi: Changed formatting of doi	22
	\section: Changed font	21	v1.32	\enddoc@text: Changed spelling of ‘Acknowledgments’ (Joe Salerno)	19
	\subsection: Changed font	21	v1.33	General: Bibliography change: avoid URLs that duplicate dois	1
	\subsubsection: Changed font	21	v1.34	\@setaddresses: Deleted thin spaces before :	20
v1.20	\@makefnmark: Redefined	22	v1.35	\oddsidemargin: Changed margins	11
v1.21	\paperUrl: Added macro	14	v1.36	General: New bib formatting	1
	\RESP@write@paper@info: Added paperUrl	18	v1.37	General: More tweaks to bib formatting	1
v1.22	General: Now we add empty even page at the end for printed version only	21	v1.38	General: No longer using lastpage package	10
v1.23	General: Switched to twoside mode of amsart	9		Rewrote code for last page, removing the dependency on the lastpage package	21
	\oddsidemargin: Made even- and odd- side margins different, except in screen and forthcoming modes	11	v1.39	\RESP@write@paper@info: Updated for the new version of last page calculation	18
	\pdfpaperheight: Added to paper width to accomodate larger thumb side margins	11	v1.4	General: Added footmisc package with ‘bottom’ option	10
v1.24	General: New command: authornote	1		Added screen option	1
	\@setauthors: Added authornotes	17		Changed bibsection font	10
	\authornote: Added command	16			
v1.25	\oddsidemargin: Changed margins	11			
	\pdfpaperheight: Returned to old page width	11			
v1.26	\@settitle: Added itscshape	16			
v1.27	General: New command: ensquote	1			

Changed color of “Author’s proof’ mark	12	<code>\enddoc@text</code> : Added flag	19
<code>\@makefntext</code> : Redefined	22	<code>\if@enddoc</code> : Added macro	19
<code>\EditorialComment</code> : Changed color	22	<code>\RESP@linecount</code> : Changed color	12
Changed font	22	v1.6 General: Changed bib style	1
<code>\ifRESP@screen</code> : Added option . . .	9	v1.7 General: Added new bibliography fields	1
<code>\paragraph</code> : Moved to LaTeX default	21	Changed formatting of doi	12
<code>\pdfpaperheight</code> : Changed paper in the manuscript mode	11	<code>\doi</code> : Changed formatting	22
<code>\RESP@linecount</code> : Changed color . . .	12	<code>\footskip</code> : Decreased to fit doi number	11
<code>\subparagraph</code> : Moved to LaTeX default	21	v1.8 General: Added blank last page if the last page is odd	1
v1.5 General: Changed color for headers and footers	12	<code>\enddoc@text</code> : Changed bibliography	19
Color change for links	1	<code>\sf@size</code> : Added definition	19
Hyperfootnotes are incompatible with hyperref	10	v1.9 <code>\@setaddresses</code> : Added penalties	20
<code>\@makefntext</code> : Added writing the current footnote page to the aux file	22	<code>\copyrightnote</code> : Made bullet disappear at break	15
<code>\EditorialComment</code> : Changed color	22	<code>\RESP@bulletboxwidth</code> : Added macro	15

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols		
\,	577	\@makefnmark 455, <u>561</u> , 562
\@and	338	\@makefntext <u>562</u>
\@par	377	\@maketitle 357, <u>368</u> , 432
\@MM	472, 473, 572	\@maketitle@hook . . 354
\@adminfootnotes . .		\@manuscriptid
.	370, <u>429</u>	 218, 232, 235
\@afterheading . .	99, 446	\@minus 519,
\@authornotes		523, 527, 531, 535
.	317, 319, 320, 343	\@mkboth 371
\@auxout	503	\@mparswitch <u>538</u>
\@cleartopmattertags		\@mparswitchfalse . 538
.	<u>430</u>	\@nameuse 443, 448
\@commby	436	\@ne 132, 134
\@copyrightnote . . .		\@nx 311,
.	169, 188, 197, 285	312, 361, 362, 371
\@copyrightyear . . .		\@onlinedate . . 189, <u>281</u>
.	277, 287, 290	\@paperUrl 237, 422, 424
\@currentlabel	574	\@par 464
\@dblarg	311	\@parboxrestore . . . 573
\@dedicatory		\@percentchar
.	374, 377, 437	 405, 407, 409,
\@doinumber	166,	411, 413, 415,
167, 185, 186,		417, 419, 421, 424
194, 195, 231, 421		\@plus 269, 519,
\@empty 166, 177, 179,		520, 523, 524,
180, 181, 185,		527, 528, 531, 535
194, 207, 232,		\@seccntformat <u>515</u>
245, 287, 290,		\@secpenalty 98, 445
293, 298, 304,		\@setabstract . . 275, 380
315, 319, 331,		\@setabstracta 275
351, 373, 374,		\@setaddresses 468, <u>471</u>
422, 453, 467, 468		\@setauthors . . <u>330</u> , 373
\@enddocfalse	450	\@setcopyright 349
\@enddoctrue	452	\@setthanks 464
\@fnsymbol	324, 342	\@settitle <u>321</u> , 372
\@footnotetext 463, 567		\@settranslators . . 467
\@for	545, 553	\@startsection 518,
\@ifnotempty	303,	522, 526, 530, 534
482, 485, 486,		\@subjclass 438
489, 490, 493, 494		\@tempa 244,
\@keywords	438	245, 360, 363,
\@mainaux	564	396, 399, 403, 419
\@mainrpi	<u>389</u> , 393,	\@tempc 398, 399
394, 402, 404,		\@tempcnta 132, 133,
406, 408, 410,		134, 249, 250,
412, 414, 416,		251, 252, 458, 459
418, 420, 423, 426		\@temptokena . . 358, 362
		\@textsuperscript . . 561
		\@thefnmark 456, 561, 575
		\@title 326,
		327, 403, 407, 432
		\@titlenotes
		 313, 315, 316, 326
		\@topnum 348
		\@topsep 335, 336
		\@translators 467
		\@undefined 325, 395, 457
		\@xaddress 433
		\@xauthor 433
		\@xcurraddr 435
		\@xemail 435
		\@xp 312, 358
		\@xtitle 432
		\\ 133, 166,
		168, 185, 187,
		194, 196, 341, 359
		A
		\abbrevcurrentmonth
		 206, 207
		\abstract <u>259</u>
		abstract (env.) 4
		\abstractbox 264
		\abstractname 272
		\addpenalty 98, 445
		\address 3, 433, 480
		\addresses 293,
		294, 296, 468, 496
		\addtocounter . . 501, 507
		\AddtoEndMatter . . .
		 7, <u>92</u> , 97, 448
		\addvspace 98, 445, 477
		\advance 134,
		250, 251, 336, 385
		\and 301, 307, 401
		\andify 352
		\arabic 502
		\articleentry . . <u>249</u> , 403
		\AtBeginDocument . . 103
		\AtEndDocument . . 95, 499
		\author 3, <u>292</u> , 433, 476
		\author@andify 339
		\authornote 4, <u>317</u>

\authors 298, 299, 301, 331, 339, 340, 343, 373, 403, 405	\curraddr .. 3, 435, 484	\doinumber 5, 224, 231, 232
	\curraddrname 485	\dp 571
	\currentissue 164, 179, 192, 201, 233, 413	E
B	\currentmonth . 165, 180, 183, 193, 205	\EC@level 545, 547
\baselineskip 322, 336, 376, 385	\CurrentOption . 49, 50, 51, 52, 53, 66	\ECSelect 5, <u>544</u>
\begin 142, 145, 158, 214, 217, 224, 230, 321	\currentpaper 209, 233, 415	\edef . 311, 360, 396, 399
\begingroup 332, 356, 472, 480, 484, 488, 492, 500, 556	\currentvolume 164, 177, 178, 192, 199, 233, 411	\EditorialComment 5, <u>539</u> , 547
\bfdefault 85	\currentyear 165, 181, 183, 193, 203, 233, 287, 290, 409	\egroup 274, 428, 465, 543, 558
\bfseries 521, 525, 533, 537	D	\else 74, 75, 76, 77, 90, 102, 166, 173, 177, 179, 181, 182, 185, 190, 194, 234, 246, 251, 279, 287, 290, 295, 300, 306, 316, 320, 325, 331, 352, 373, 375, 384, 397, 422, 453, 457, 467, 468, 509, 510, 511, 512, 541, 550, 563
\bgroup 264, 391, 454, 541, 554	\DeclareOptionX 49, 50, 51, 52, 53, 56, 59, 62, 65, 66	\em 325
\bibfont 100	\dedicatory 437	\email 3, 435, 488
\bibliography 96, 97, 452	\def 46, 90, 91, 92, 97, 98, 100, 199, 201, 203, 209, 218, 231, 237, 239, 240, 242, 244, 245, 246, 247, 249, 253, 277, 281, 285, 313, 314, 317, 318, 321, 325, 330, 333, 338, 341, 347, 359, 368, 390, 398, 401, 429, 430, 431, 439, 451, 452, 464, 470, 471, 476, 480, 484, 488, 492, 502, 515, 544, 556, 557, 560, 561, 562, 567	\emailaddrname <u>470</u> , 489
\bibliographystyle . 95		\end 144, 147, 160, 212, 221, 328
\bibsection 98		\end@page . 193, 245, 246
\bigskipamount 98, 189, 445, 477		\endcsname ... 312, 516, 540, 547, 550, 551, 554, 575
\bodyfont <u>10</u>		\enddoc@text ... 92, <u>451</u>
bodyfont (option) 2		\endgroup . 345, 364, 483, 487, 491, 495, 497, 508, 557
C		\endlist 274
\c@footnote 324, 342, 365		\endpage ... 4, <u>244</u> , 247
\c@page ... 241, 459, 565		\endtrivlist 344
\centering ... 335, 377		\enquote 7
\cfoot 163, 175, 191		\enspace 516
\changes 215, 225, 226, 228		\ensquote 7
\chead 170		environments:
\ClassInfo 254		abstract 4
\ClassWarning 47, 257, 261		notes 6
\cleaders 288		\evensidemargin ... <u>108</u>
\cleardoublepage .. 513		\everypar 366
\clearpage 499		\expandafter .. 399, 540, 546, 550, 553
\closeout 426		F
\clubpenalty 472		\fancyfoot 138, 150, 153
\color 133, 150, 153, 170, 542, 558		
\columnwidth 572		
\commby 436		
\contrib 434		
\contribs 434		
\copyrightnote .. 4, <u>285</u>		
\copyrightyear .. 4, <u>277</u>		
\cs 226		
\csname 312, 516, 540, 546, 550, 551, 554, 575		
	\curraddr .. 3, 435, 484	
	\curraddrname 485	
	\currentissue 164, 179, 192, 201, 233, 413	
	\currentmonth . 165, 180, 183, 193, 205	
	\CurrentOption . 49, 50, 51, 52, 53, 66	
	\currentpaper 209, 233, 415	
	\currentvolume 164, 177, 178, 192, 199, 233, 411	
	\currentyear 165, 181, 183, 193, 203, 233, 287, 290, 409	
	D	
	\DeclareOptionX 49, 50, 51, 52, 53, 56, 59, 62, 65, 66	
	\dedicatory 437	
	\def 46, 90, 91, 92, 97, 98, 100, 199, 201, 203, 209, 218, 231, 237, 239, 240, 242, 244, 245, 246, 247, 249, 253, 277, 281, 285, 313, 314, 317, 318, 321, 325, 330, 333, 338, 341, 347, 359, 368, 390, 398, 401, 429, 430, 431, 439, 451, 452, 464, 470, 471, 476, 480, 484, 488, 492, 502, 515, 544, 556, 557, 560, 561, 562, 567	
	\define@boolkey ... 42	
	\define@choicekey 10, 26	
	\definecollection . 441	
	\dimen@ 385, 386	
	\dimen@i 378	
	\do .. 431, 432, 433, 434, 435, 436, 437, 438, 545, 553	
	\doi .. 167, 186, 195, <u>560</u>	
	\doinumber 5, 224, 231, 232	
	\dp 571	
	E	
	\EC@level 545, 547	
	\ECSelect 5, <u>544</u>	
	\edef . 311, 360, 396, 399	
	\EditorialComment 5, <u>539</u> , 547	
	\egroup 274, 428, 465, 543, 558	
	\else 74, 75, 76, 77, 90, 102, 166, 173, 177, 179, 181, 182, 185, 190, 194, 234, 246, 251, 279, 287, 290, 295, 300, 306, 316, 320, 325, 331, 352, 373, 375, 384, 397, 422, 453, 457, 467, 468, 509, 510, 511, 512, 541, 550, 563	
	\em 325	
	\email 3, 435, 488	
	\emailaddrname <u>470</u> , 489	
	\end 144, 147, 160, 212, 221, 328	
	\end@page . 193, 245, 246	
	\endcsname ... 312, 516, 540, 547, 550, 551, 554, 575	
	\enddoc@text ... 92, <u>451</u>	
	\endgroup . 345, 364, 483, 487, 491, 495, 497, 508, 557	
	\endlist 274	
	\endpage ... 4, <u>244</u> , 247	
	\endtrivlist 344	
	\enquote 7	
	\enspace 516	
	\ensquote 7	
	environments:	
	abstract 4	
	notes 6	
	\evensidemargin ... <u>108</u>	
	\everypar 366	
	\expandafter .. 399, 540, 546, 550, 553	
	F	
	\fancyfoot 138, 150, 153	

\fancyhead ... 137, 139, 140, 142, 145	\headsep 120	\immediate ... 503, 564
\fancyhf 156	\href 491	\includecollection . 448
\fancypagestyle ... 155	\hsize 572	\indent ... 485, 489, 493
\fi .. 23, 39, 78, 80, 86, 88, 91, 101, 105, 113, 117, 127, 128, 135, 148, 151, 154, 161, 167, 178, 179, 181, 184, 186, 195, 198, 207, 236, 243, 246, 251, 263, 275, 280, 287, 290, 297, 302, 308, 316, 320, 325, 346, 353, 373, 379, 387, 400, 425, 427, 461, 462, 466, 467, 468, 477, 505, 514, 543, 548, 551, 559, 566	\hskip 288	\input 256
\floatingpenalty .. 572	\hspace 282	\insert 460, 568
\flushright 472	\Hy@colorlink 556	\interfootnotelinepenalty 570
\footins 460, 568	\Hy@colorlinksfalse 555	\interlinepenalty 472, 570
\footnote 315, 316, 319, 320	\Hy@endcolorlink .. 557	\issuenumber 4, 201
\footnotesep .. 571, 577	\Hy@temp 502, 505	\item 272, 337
\footnotesize 139, 140, 144, 163, 175, 189, 191, 335, 377, 569	\hypersetup .. 74, 75, 76, 77, 78, 327, 340	\itemindent 268
\footrulewidth 122		\itscshape 325
\footskip 124		\itshape 139, 144, 163, 176, 191, 192, 377, 529
forthcoming (option) . 3		
\fullwidthdisplay . 270		
	I	J
	\if@enddoc ... 449, 563	\jobname 393
	\if@fileswh 392	
	\if@titlepage 382	K
	\ifcase 12, 28	\keywords 438
	\IfFileExists 80, 88, 253	
	\ifHy@pageanchor .. 505	L
	\ifnum 134, 241, 459	\labelwidth 266
	\ifodd 251	\LARGE 323
	\ifRESP@firstingroup 469, 476	\large 343, 521
	\ifRESP@fontauto . 2, 79	\lastbox 366
	\ifRESP@forthcoming 63, 77, 114, 174, 278, 512	\lastfootnote@page 457, 458, 565
	\ifRESP@lsabon ... 6, 81	\leftmargin 267
	\ifRESP@manuscript . 54, 74, 102, 127, 149, 509, 544, 552	\let ... 96, 270, 351, 431, 455, 456, 464
	\ifRESP@mtshadow . 8, 89	\lhead 158, 189
	\ifRESP@natbib 93	\linebreak 341
	\ifRESP@preprint 60, 76, 128, 152, 162, 511	\list 266
	\ifRESP@printlinecount . 125, 129, 141, 157	\listisep 119
	\ifRESP@rpfontauto 4, 87	\listparindent 268
	\ifRESP@screen 57, 75, 110, 510	\LoadClass 68
		\long 46, 567
		\loop 133
G		M
\g@addto@macro 92, 296, 301, 307, 316, 320	\ifx 166, 177, 179, 180, 181, 185, 194, 207, 232, 245, 260, 275, 287, 290, 293, 298, 304, 315, 319, 325, 331, 351, 373, 374, 395, 422, 453, 457, 467, 468, 540, 550	\makeatletter 444
\gdef 205, 206, 207, 218, 231, 237, 281, 294, 299, 305, 315, 319, 546, 554	\ignorespaces 359, 482, 483, 486, 490, 494, 577	\makeatother 447
\global 264, 378		\maketitle 4, 260, 262, 347, 432
		\MakeUppercase 362
		manuscript (option) .. 2
		\manuscriptid 5, 214, 218, 219
		\marginpar 542
H		\marginparwidth ... 542
\hbox 288, 561		\markboth 361
\headheight 121		\medskip 460
\headrulewidth 122		

<code>\medskipamount</code>	<code>\pagestyle</code> 136	<code>\renewenvironment</code> . 259
. 99, 119, 446	<code>\papernumber</code> 4, 209	<code>\repeat</code> 134
	<code>\paperurl</code> 5, 237	<code>\RequirePackage</code> 1, 69,
	<code>\par</code> 98, 99,	70, 72, 82, 83, 94
	347, 445, 446,	<code>\RESP@bibliography</code> .
	464, 471, 476,	 96, 97, 452
	478, 481, 483,	<code>\RESP@bulletboxwidth</code>
	487, 491, 495, 577	 283, 288
	<code>\paragraph</code> 530	<code>\RESP@firstgroupfalse</code>
	<code>\parbox</code> 131, 189	 478
	<code>\parindent</code> 479, 534, 573	<code>\RESP@firstgrouptrue</code>
	<code>\parsep</code> 269	 474,
	<code>\PassOptionsToClass</code> 66	480, 484, 488, 492
	<code>\PassOptionsToPackage</code>	<code>\RESP@fontautofalse</code>
	 71	 15, 18, 21
	<code>\pdfpageheight</code> 104	<code>\RESP@fontautotruer</code> .
	<code>\pdfpagewidth</code> 103	 3, 13, 25
	<code>\pdfpaperheight</code> . . . 102	<code>\RESP@forthcomingfalse</code>
	<code>\pdfpaperwidth</code> 102	 64
	<code>\penalty</code> 477	<code>\RESP@forthcomingtrue</code>
	<code>preprint</code> (option) 3	 65
	<code>\prevdepth</code> 378	<code>\RESP@linecount</code> . . .
	<code>\prevpaper</code> 5, 253	 129, 143, 146, 159
	<code>\ProcessOptionsX</code> . . . 67	<code>\RESP@lsabonfalse</code> . .
	<code>\protect</code> . . . 262, 333, 341	 7, 22, 80
	<code>\protected@edef</code> . . . 574	<code>\RESP@lsabontrue</code> . . .
	<code>\protected@write</code> 402,	 16, 19, 80
	404, 406, 408,	<code>\RESP@manuscriptfalse</code>
	410, 412, 414,	 55
	416, 418, 420, 423	<code>\RESP@manuscripttrue</code> 56
	<code>\publicationmonth</code> 4, 205	<code>\RESP@mtshadowfalse</code>
	<code>\publicationyear</code> 4, 203	 9, 38, 88
	<code>\put</code> 143, 146, 159	<code>\RESP@mtshadowtrue</code> .
		 32, 35, 88
		<code>\RESP@natbibtrue</code> . . 45
		<code>\RESP@preprintfalse</code> 61
		<code>\RESP@preprinttrue</code> . 62
		<code>\RESP@printlinecount</code>
		 125
		<code>\RESP@printlinecountfalse</code>
		 126
		<code>\RESP@printlinecounttrue</code>
		 127, 128
		<code>\RESP@rpfontautofalse</code>
		 31, 34, 37
		<code>\RESP@rpfontautotruer</code>
		 5, 29, 41
		<code>\RESP@screenfalse</code> . . 58
		<code>\RESP@screentruer</code> . . 59
		<code>\RESP@size@warning</code> .
		 46,
		49, 50, 51, 52, 53
		<code>\RESP@write@paper@info</code>
		 355, 390
N		
<code>\natbib</code> 42		
<code>natbib</code> (option) 3		
<code>\newcommand</code>		
. 205, 539, 549, 552		
<code>\newenvironment</code> . . . 442		
<code>\newif</code> 2, 4, 6, 8, 54, 57,		
60, 63, 125, 449, 469		
<code>\newlabel</code> 504		
<code>\newlength</code> 283		
<code>\newpage</code> 383		
<code>\newsavebox</code> 130		
<code>\newwrite</code> 389		
<code>\nobreak</code> 99, 446,		
472, 476, 478,		
481, 485, 489, 493		
<code>\noindent</code> 99, 446, 562		
<code>\nolinkurl</code> 491		
<code>\normalfont</code> 272,		
343, 369, 521,		
525, 529, 533,		
537, 561, 569, 578		
<code>\normalparindent</code> . . .		
. 268, 573		
<code>\normalsize</code> 272,		
369, 381, 525,		
529, 533, 537, 578		
<code>\notes</code> 441		
<code>notes</code> (env.) 6		
<code>\nr</code> 10, 12, 26, 28		
O		
<code>\oddsidemargin</code> 108		
<code>\onlinedate</code> 3, 281		
<code>\openout</code> 393		
options:		
<code>bodyfont</code> 2		
<code>forthcoming</code> 3		
<code>manuscript</code> 2		
<code>natbib</code> 3		
<code>preprint</code> 3		
<code>screen</code> 3		
<code>\or</code> 14, 17, 20, 30, 33, 36		
P		
<code>\p@</code> 269, 322, 335, 376, 385		
<code>\PackageWarning</code> . . .		
. 24, 40, 43		
<code>\pagenumbering</code> 239, 241		
<code>\pageref</code> 245		
<code>\pagespan</code> 247		
Q		
<code>\qqquad</code> 139, 140, 144		
<code>\quad</code> 284, 288, 464		
R		
<code>\r@RP@LastPage</code> 395, 399		
<code>\raggedbottom</code> 578		
<code>\raggeddright</code> . . . 189, 543		
<code>\raisebox</code> 189		
<code>\relax</code> 12, 28, 132,		
249, 250, 251,		
260, 270, 275,		
322, 331, 335,		
337, 386, 394,		
431, 455, 456,		
458, 459, 540, 550		
<code>\renewcommand</code> 84, 85,		
122, 123, 292,		
324, 342, 518,		
522, 526, 530, 534		

